

CAPETOWN Recessed



Manufacture: NEKO LIGHTING AG

Type: CAPETOWN Recessed Step Light CTRR-8306505F-DN

General

- Outdoor
- Recessed
- Fixed
- Step Light
- Version: round
- Housing: Dark-Grey
- IP 65

LED


- 3000K
- CRI 80
- System Output: 150lm
- 50000h@L80B10




Description

Recessed Step Light round made of die-cast aluminium with integrated ON-OFF Driver; dark-grey powder-coating finish (RAL 7024); LED 3W; measurement Ø115mm; depth of the luminaire is 37mm; cutout of Ø110mm x 55mm; luminaire's weight is approximately 300g; CCT 3000K with a System Output of 150lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient EDISON LED Chips; 3 years warranty; beam characteristic with 65° beam angle; degree of housing protection according to DIN EN 60529 (IP65); Impact resistance of the luminaire is in the class IK07;

Light distribution



Technical drawing



Optics

- Beam angle: 65°

Electric

- LED Driver: ON-OFF
- LED Power: 3W
- System Power: 4.5W
- 220-240 VAC

Dimensions

- Measurement: Ø115mm
- Cutout: Ø110mm x 55mm
- Height: 37mm
- Net Weight: 300g
- Gross Weight: 360g



RoHS



The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.