


IG-63-47R



InGround LED Spot $\overbrace{\text{Dimmable}}^{\text{Inground}} \overbrace{\text{Source}}^{\text{Source}} \overbrace{\text{Source}}^{\text{Source}} \overbrace{\text{Life Span}}^{\text{Source}} \overbrace{\text{Life Span}$



Inground LED spot



- 3W Max
- IP67 for wet locations
- ✓ 50,000 hour lifetime
- CNC processed Aluminum housing
- 500Kg walkover
- Installation accessories supplied

SPECIFICATIONS

Power	1 LED X 3W (700mA)
Light Color	White: Warm, Neutral, Cool Color: Red, Green, Blue, Amber
White light CCT	3,000К 4,000К 6,000К
Lumen Output ¹	160lm 160lm 260lm
White light CRI ²	≥80 - Standard ≥90
Beam	5°, 15°, 25°, 45°, Wide (frosted)
Optics	20mm Optics Clear or frosted cover

Diameter	ø63
Installation cut off	Ø48mm (without concrete box)
Height	26.5mm (without PG and cable)
Weight	130g

Housing	Aluminum, tempered crystal glass cover
Housing color	Natural anodize coating
IP Rating	Wet locations - IP67
Operating Temp.	-20°C to 40°C
Cable	50cm Neoprene cable - Standard
Connectors	Open Wires
Accessories	B-47 - Concrete box (ø50.5 mm × 80mm)

Extras

Accessories	S-30 wood / plaster installation spring (12mm)
Cable	Custom cable length up to 50m
Power Supply	Constant Current
Control	On/Off 0-10V Triac DMX DALI

Notes:

1 LEDs have $\pm 10\%$ output tolerance in accordance to manufacturer specifications


2 CRI 90 version is available upon request only

3 Extras are not supplied by default and priced separately






DRAWINGS



SIDE

TOP





www.led-design.co.il Specifications may change without notice Copyright © 2018 Led Lighting Solutions LTD, All rights reserved