Datasheet

CAPETOWN Recessed

Manufacture: NEKO LIGHTING AG

Type: CAPETOWN Recessed Step Light CTSR-8306505F-DN



General

- Outdoor
- Recessed
- Fixed
- Step Light
- Version: square
- Housing: Dark-Grey
- IP 65

LED



• 3000K • CRI 80

System Output: 160lm50000h@L80B10

Optics

• Beam angle: 65°

Electric

LED Driver: ON-OFFLED Power: 3WSystem Power: 4.5W220-240 VAC

Dimensions


Measurement: 115mm x 115mmCutout: 110mm x 110mm x 55mm

Height: 37mmNet Weight: 340gGross Weight: 400g


Description

Recessed Step Light square made of die-cast aluminium with integrated ON-OFF Driver; dark-grey powder-coating finish (RAL 7024); LED 3W; measurement 115mm x 115mm; deepth of the luminaire is 37mm; cutout of 110mm x 110mm x 55mm; luminaire's weight is approximately 340g; CCT 3000K with an System Output of 160lm; decent color rendering at an index of CRI80; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient EDISON LED Chips; 3 years warranty; beam characteristic with 65° beam angle; degree of housing protection according to DIN EN 60529 (IP65); Impact resistance of the luminaire is in the class IK07;

Light distribution



Technical drawing















The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of NEKO Lighting AG apply.

